

Ashley Polymers Ashlene® 520-25G Nylon 66, 25% Glass Reinforced

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, 30% Glass Fiber Filled

Material Notes:

Nylon 66, 25% glass reinforced.Data provided by the manufacturer

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ashley-Polymers-Ashlene-520-25G-Nylon-66-25-Glass-Reinforced.php

Physical Properties	Metric	English	Comments
Density	1.31 g/cc	0.0473 lb/in³	ASTM D792
Water Absorption	1.1 %	1.1 %	ASTM D570
Linear Mold Shrinkage	0.0030 cm/cm	0.0030 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	120	120	ASTM D785
Tensile Strength, Ultimate	124 MPa	18000 psi	ATSM D638
Elongation at Break	3.0 %	3.0 %	
Flexural Modulus	6.60 GPa	957 ksi	ASTM D790
Izod Impact, Notched	0.960 J/cm	1.80 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	252 °C	486 °F	ASTM D3418
Deflection Temperature at 0.46 MPa (66 psi)	246 °C	475 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	238 °C	460 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China