

Ashley Polymers Ashlene® 527LD-13G Nylon 66, 13% Glass Reinforced

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, 10% Glass Fiber Filled

Material Notes:

A high impact 13% glass reinforced Nylon 66.Data provided by the manufacturer

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ashley-Polymers-Ashlene-527LD-13G-Nylon-66-13-Glass-Reinforced.php

Physical Properties	Metric	English	Comments
Density	1.19 g/cc	0.0430 lb/in³	ASTM D792
Water Absorption	0.90 %	0.90 %	ASTM D570
Linear Mold Shrinkage	0.0080 cm/cm	0.0080 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	106	106	ASTM D785
Tensile Strength, Ultimate	94.0 MPa	13600 psi	ATSM D638
Elongation at Break	6.0 %	6.0 %	ASTM D638
Flexural Modulus	3.50 GPa	508 ksi	ASTM D790
Izod Impact, Notched	1.55 J/cm	2.90 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	254 °C	489 °F	ASTM D3418

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China