

Ashley Polymers Ashlene® RH190 Acetal

Category : Polymer , Thermoplastic , Acetal (POM) , Acetal Homopolymer, Unreinforced

Material Notes:

General purpose, reprocessed homopolymer, excellent toughness, strength, stiffness and lubricity. Available in Natural and Black. Natural: Designated RH190N-3; Black: Designated RH190B. Data provided by the manufacturer

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ashley-Polymers-Ashlene-RH190-Acetal.php

Physical Properties	Metric	English	Comments
Density	1.41 g/cc	0.0509 lb/in ³	ASTM D792
Linear Mold Shrinkage, Flow	0.022 cm/cm	0.022 in/in	ASTM D955
Linear Mold Shrinkage, Transverse	0.018 cm/cm	0.018 in/in	ASTM D955
Melt Flow	8.0 - 11 g/10 min	8.0 - 11 g/10 min	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	62.0 MPa	8990 psi	ASTM D638
Elongation at Break	18 %	18 %	ASTM D638
Flexural Modulus	2.60 GPa	377 ksi	ASTM D790
Izod Impact, Notched	0.640 J/cm	1.20 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	165 °C	329 °F	ASTM D3418
Deflection Temperature at 1.8 MPa (264 psi)	127 °C	261 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China