

Axiall 15641 Wire & Cable Flexible PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Wire and Cable Grade

Material Notes:

Semi-rigid, fungus and microbe resistant insulation compound recommended for UL Style #1061 and CSA-SR applications. The compound has good migration and toner resistance. Information provided by Georgia Gulf Georgia Gulf became Axiall Corporation in 2013.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Axiall-15641-Wire-Cable-Flexible-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.31 - 1.35 g/cc	1.31 - 1.35 g/cc	ASTM D-792

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	57 - 63	57 - 63	delayed; ASTM D-2240
Tensile Strength, Yield	23.1 MPa	3350 psi	ASTM D-638
Elongation at Yield	276.3 %	276.3 %	Air Aging: 168 hours @ 136°C; 30 mil slabs; UL 1581
	300 %	300 %	ASTM D-638
100% Modulus	0.02051 GPa	2.975 ksi	ASTM D-638

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-8.00 °C	17.6 °F	ASTM D-746
Oxygen Index	28 %	28 %	ASTM D-638

Electrical Properties	Metric	English	Comments
Volume Resistivity	1.00e+15 ohm-cm	1.00e+15 ohm-cm	50% RH; ASTM D-257

Processing Properties	Metric	English	Comments
Melt Temperature	196 °C	385 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China