

Axiall 8916 Moldings & Extrusions Flexible PVC

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

A satin finish extrusion compound best suited for extruded T-moldings, tubings and other shapes where uniform flow through the die is required. The compound exhibits excellent abrasion resistance. Information provided by Georgia Gulf Georgia Gulf became Axiall Corporation in 2013.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Axiall-8916-Moldings-Extrusions-Flexible-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.33 - 1.37 g/cc	1.33 - 1.37 g/cc	ASTM D-792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	88 - 94	88 - 94	delayed; ASTM D-2240
Tensile Strength, Yield	20.7 MPa	3000 psi	ASTM D-638
Elongation at Yield	300 %	300 %	ASTM D-638
100% Modulus	0.0145 GPa	2.10 ksi	ASTM D-638

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-20.0 °C	-4.00 °F	ASTM D-746

Processing Properties	Metric	English	Comments
Melt Temperature	185 °C	365 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China