

BASF Lupranate® 5030 Isocyanate

Category : Fluid

Material Notes:

Description: Lupranate® 5030 Isocyanate is a liquid urethane modified diphenylmethane diisocyanate. Lupranate 5030 Isocyanate is used in conjunction with high molecular weight polyester or polyether polyols and short chain diols for the manufacture of high quality flexible and semi flexible elastomers and integral skin foams. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Lupranate-5030-Isocyanate.php

Physical Properties	Metric	English	Comments
Density	1.17 g/cc	0.0423 lb/in ³	
Viscosity	1130 cP	1130 cP	
Vapor Pressure	<= 1.33e-8 bar @Temperature 25.0 °C	<= 0.00000998 torr @Temperature 77.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	>= 190 °C @Pressure 0.000667 MPa	>= 374 °F @Pressure 0.0967 psi	
Flash Point	>= 200 °C	>= 392 °F	

Descriptive Properties	Value	Comments
Color	Light Yellow	
Composition	NCO content	0.189

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China