

BASF Pluracol® 1168 Rigid Polyol

Category : Fluid

Material Notes:

Description: Pluracol® 1168 Polyol is a general purpose aromatic initiator-based polyol for rigid foams for use in a variety of applications. It is attractively priced for consideration for foaming insulated panels, refrigerators, trailers, furniture, etc., by pour-in-place or frothing techniques. Foams made with Pluracol 1168 Polyol are characterized by fine cell structure, low K factor, and good dimensional stability. Pluracol 1168 Polyol is not recommended for use in quasi-prepolymer preparation. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Pluracol-1168-Rigid-Polyol.php

Physical Properties	Metric	English	Comments
Density	1.059 g/cc	0.03826 lb/in ³	
	@Temperature 45.0 °C	@Temperature 113 °F	
	1.063 g/cc	0.03840 lb/in ³	
	@Temperature 35.0 °C	@Temperature 95.0 °F	
	1.067 g/cc	0.03855 lb/in ³	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity	357 cP	357 cP	
	@Temperature 45.0 °C	@Temperature 113 °F	
	758 cP	758 cP	
	@Temperature 35.0 °C	@Temperature 95.0 °F	
	1880 cP	1880 cP	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.10 %	<= 0.10 %	STI 3062

Descriptive Properties	Value	Comments
Color	Amber Liquid	
Hydroxyl Number	285 - 315 mg KOH/g	STI 3007/3162

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China