

BASF Pluracol® 1578 Rigid Polyol

Category : Fluid

Material Notes:

Description: Pluracol® 1578 polyol is a general purpose aromatic initiator-based polyol for rigid foams for use in a variety of applications. It is attractively priced for consideration for foaming insulated panels, refrigerators, trailers, furniture, etc., by pour-in-place or frothing techniques. Foams made with Pluracol 1578 are characterized by fine cell structure, low K factor, and good dimensional stability. Pluracol 1578 is not recommended for use in quasi-prepolymer preparation. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Pluracol-1578-Rigid-Polyol.php

Physical Properties	Metric	English	Comments
Density	1.062 g/cc	0.03837 lb/in ³	
	@Temperature 70.0 °C	@Temperature 158 °F	
	1.069 g/cc	0.03862 lb/in ³	
	@Temperature 40.0 °C	@Temperature 104 °F	
	1.075 g/cc	0.03884 lb/in ³	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity	224 cP	224 cP	
	@Temperature 70.0 °C	@Temperature 158 °F	
	3000 cP	3000 cP	
	@Temperature 40.0 °C	@Temperature 104 °F	
	18600 cP	18600 cP	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.050 %	<= 0.050 %	STI 3062

Descriptive Properties	Value	Comments
Color	Amber Liquid	
Hydroxyl Number	380-410 mg KOH/g	STI 3007/3162

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China