

BASF Polyetheramine D 2000

Category : Polymer

Material Notes:

Description: Polyetheramine D 2000 is a yellowish liquid, with an emine-like odor. It is partly miscible with water and other solvents. Applications: Intermediate used in the production of: Plastics, Coatings Industry (polyurea systems), Adhesives, and Rim formulations. Also used as a: Curing agent for epoxy resins. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Polyetheramine-D-2000.php

Physical Properties	Metric	English	Comments
Density	0.9978 g/cc	0.03605 lb/in ³	
Molecular Weight	2000 g/mol	2000 g/mol	

Thermal Properties	Metric	English	Comments
Melting Point	-29.0 °C	-20.2 °F	Freezing Point
Boiling Point	>= 250 °C	>= 482 °F	
Flash Point	>= 234 °C	>= 453 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.25 %	<= 0.25 %	DIN 51 777

Descriptive Properties	Value	Comments
Acetyl Number	55.0-61.7 mg KOH/g	BASF Method
Amine Number	53.3-58.9 mg KOH/g	BASF Method
Assay, Primary Amines	0.97	BASF Method
Color	<50	APHA, DIN EN 1557
Ignition Temperature	330°C	
Total Amines	0.97-1.05 meq/g	BASF Method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China