

BASF Ultradur® B 4500 BK 00110 PBT

Category : Polymer , Thermoplastic , Polyester, TP , Polybutylene Terephthalate (PBT)

Material Notes:

Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Ultradur-B-4500-BK-00110-PBT.php

Physical Properties	Metric	English	Comments
Bulk Density	0.600 - 0.900 g/cc	0.0217 - 0.0325 lb/in ³	
Density	1.20 - 1.35 g/cc	0.0434 - 0.0488 lb/in ³	ISO 1183

Thermal Properties	Metric	English	Comments
Specific Heat Capacity	1.50 J/g-°C	0.359 BTU/lb-°F	IEC 1006
Melting Point	220 - 230 °C	428 - 446 °F	DIN 53736
Decomposition Temperature	>= 290 °C	>= 554 °F	

Descriptive Properties	Value	Comments
Color	BK 00110	
Commercial Status	Europe	
Ignition Temperature	350°C	ASTM D1929

Contact Songhan Plastic Technology Co.,Ltd.Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China