

Bales Mold Service Hard Chrome QQ-C-320 Mold Coating

Category: Metal, Other Engineering Material, Ceramic/Metallic Coating

Material Notes:

Description: Hard Chrome provides excellent wear resistance to glass filled resins. It can be selectively plated up to .020 for shims and inside or outside diameter corrections that need E.D.M. or grinding to finished size. Hard Chrome is a great way to save precision pieces that cannot be welded. Information provided by Bales Mold Service Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Bales-Mold-Service-Hard-Chrome-QQ-C-320-Mold-Coating.php

| Mechanical Properties | Metric | English | Comments |
|-------------------------|---------|---------|----------|
| Hardness, Rockwell C | 72 | 72 | |
| Coefficient of Friction | <= 0.20 | <= 0.20 | |

| Processing Properties | Metric | English | Comments |
|------------------------|---------|---------|---------------------|
| Processing Temperature | 54.4 °C | 130 °F | Applied Temperature |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China