

Bapolan® 6403 Polystyrene, Extrusion Grade

Category : Polymer , Thermoplastic , Polystyrene (PS)

Material Notes:

Bapolan PS6403 is a high impact polystyrene resin designed for extrusion-thermoforming applications. It complies with US FDA21 CFR177.1640 and 94HB UL rating.Applications: General purpose, housewares, and housing.Bapolene® and Bapolan® are registered trademarks of Bamberger Polymers, Inc. Information provided by Bamberger Polymers. All data is based on molded plaques.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Bapolan-6403-Polystyrene-Extrusion-Grade.php

Physical Properties	Metric	English	Comments
Melt Flow	3.0 g/10 min	3.0 g/10 min	200C°/5,000g; ASTM D-1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	24.5 MPa	3550 psi	ASTM D-638
Elongation at Yield	46 %	46 %	ASTM D-638
Flexural Modulus, 1% Secant	2206 MPa	320000 psi	ASTM D-790A
Izod Impact, Notched	1.07 J/cm	2.00 ft-lb/in	ASTM D-256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	93.0 °C	199 °F	ASTM D-648

Descriptive Properties	Value	Comments
Process	Extrusion	
Region	Europe/Turkey	Bamberger Polymers Distribution
	International	Bamberger Polymers Distribution
	Mexico	Bamberger Polymers Distribution
	US & Canada	Bamberger Polymers Distribution

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China