

Borealis CG8410 High Density Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE

Material Notes:

CG8410 is a high-density polyethylene for extrusion coating. Applications: extrusion coating of high volume production of boards and papers. Information provided by Borealis AG

Order this product through the following link:

http://www.lookpolymers.com/polymer_Borealis-CG8410-High-Density-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.941 g/cc	0.0340 lb/in ³	ISO 1183
Melt Flow	7.5 g/10 min @Load 2.16 kg, Temperature 190 °C	7.5 g/10 min @Load 4.76 lb, Temperature 374 °F	ISO 1133
Neck In	9.50 cm	3.74 in	BTM 14920
Coating Weight	>= 8.00 g/m ²	>= 5.00 lb/ream	BTM 14922

Descriptive Properties	Value	Comments
Coating Speed (m/min)	< 500	BTM 14921

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China