

Braskem TI4015F2 Impact Copolymer Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene Copolymer

Material Notes:

Description: Superior balance of stiffness and impact strength. Applications: Suggested uses include extrusion applications requiring good impact strength. Process: Extrusion. This resin meets the requirements for olefin polymers as defined in 21 CFR, section 177.1520 issued by the Food and Drug Administration. The additives present are covered in appropriate regulation by FDA. Information provided by Braskem

Order this product through the following link:

http://www.lookpolymers.com/polymer_Braskem-TI4015F2-Impact-Copolymer-Polypropylene.php

Physical Properties	Metric	English	Comments
Melt Flow	1.6 g/10 min	1.6 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Tensile Strength	26.2 MPa	3800 psi	2 in/min; ASTM D638
Elongation at Yield	17 %	17 %	2 in/min; ASTM D638
Flexural Modulus	1.24 GPa	180 ksi	0.05 in/min, 1% secant; ASTM D-790A
Izod Impact, Notched	NB	NB	ASTM D256A
Gardner Impact	28.5 J	21.0 ft-lb	ASTM D5420G

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China