

Buckeye Polymers BP Flex A9008 TPO

Category : Polymer , Thermoplastic , Elastomer, TPE , Thermoplastic Olefinic Elastomer (TPO)

Material Notes:

TPO's are a family of thermoplastic elastomers which exhibit rubber-like properties and are processable on conventional thermoplastic equipment. These resins have excellent UV resistance and have a wide service range from -20 degrees C to 120 degrees C, high tear resistance, low density, and good paintability.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Buckeye-Polymers-BP-Flex-A9008-TPO.php

Physical Properties	Metric	English	Comments
Density	0.960 g/cc	0.0347 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.013 cm/cm	0.013 in/in	ASTM D955
Melt Flow	8.0 g/10 min	8.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	90	90	ASTM D2240
Tensile Strength, Ultimate	8.30 MPa	1200 psi	ASTM D638
Flexural Modulus	0.200 GPa	29.0 ksi	ASTM D790
Tear Strength	63.1 kN/m	360 pli	ASTM D624

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China