

Chase Plastics CP Pryme® NN300STL (COND, 50% RH) Nylon 66 (Utility Grade), Super Toughened, Internally Lubricated

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, Impact Grade

Material Notes:

Information provided by Chase Plastics.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chase-Plastics-CP-Pryme-NN300STL-COND-50-RH-Nylon-66-Utility-Grade-Super-Toughened-Internally-Lubricated.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.06 g/cc	1.06 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	32.4 MPa	4700 psi	ASTM D638
Flexural Strength	20.0 MPa	2900 psi	ASTM D790
Flexural Modulus	0.586 GPa	85.0 ksi	ASTM D790
Izod Impact, Notched	NB	NB	ASTM D256

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China