

Cheng Yu Plastic E2330 Flame Retardant PET, 30% Glass Fiber

Category : Polymer , Thermoplastic , Polyester, TP , Polyethylene Terephthalate (PET) , Polyethylene Terephthalate (PET), 30% Glass Reinforced

Material Notes:

Order this product through the following link:

http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-E2330-Flame-Retardant-PET-30-Glass-Fiber.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.58 g/cc	1.58 g/cc	ASTM D792
Linear Mold Shrinkage	0.0020 - 0.0080 cm/cm	0.0020 - 0.0080 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	112	112	ASTM D785
Tensile Strength, Yield	1.29 MPa	188 psi	ASTM D638
Flexural Yield Strength	206 MPa	29900 psi	ASTM D790
Izod Impact, Notched	0.863 J/cm	1.62 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	245 °C	473 °F	ASTM D648
Flammability, UL94	V-0	V-0	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China