Chesterton 660 Silicone Lubricant

Category : Fluid , Lubricant , Silicone Base

Material Notes:

Description: Chesterton® 660 Silicone Lubricant is a clean, clear, silicone fluid which will provide continuous film lubrication for mechanical parts and sliding surfaces constructed of plastic, rubber or metal . Wherever porous synthetics, plastics, rubber, neoprene, wood etc. come into contact with other materials, 660 Silicone Lubricant quickly penetrates surfaces to lubricate, prevent sticking and reduce wear. The product leaves a slippery, clean film which will not stain or leave gummy residues. It will stay where it is applied and not readily be squeezed out. Chesterton 660 Silicone Lubricant is quite versatile for both high and low temperature applications. The product is effective from -40°C to 205°C (-40°F to 400°F). It is invaluable as a lubricant where petroleum oils cannot be used. Features:Braod temperature range NSF H1 - Registration number 133932 (bulk) and 133970 (aerosol)Complies with FDA regulations for incidental food contactMakes surface water resistantClean, non-stainingPenetrates fine tolerancesLong lastingInformation provided by Chesterton

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chesterton-660-Silicone-Lubricant.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.700 g/cc	0.700 g/cc	
Viscosity Measure	500 cSt	500 cSt	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	205 °C	401 °F	
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	

Descriptive Properties	Value	Comments
Appearance	Clear, colorless	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China