

Chevron Phillips 1018 Extrusion Coating Resin

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

Resin Type: High Speed Resin Characteristics: Excellent Processability, High Temperature Stability, Good Draw Down

Resin Applications: Food Packaging, Laminations, Sealant Resin Data provided by Chevron Chemical.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chevron-Phillips-1018-Extrusion-Coating-Resin.php

Physical Properties	Metric	English	Comments
Density	0.917 g/cc	0.0331 lb/in ³	ASTM D1505-60T
Melt Flow	12 g/10 min	12 g/10 min	ASTM D1238-57T

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	9.40 MPa	1360 psi	ASTM D638-61T
Tensile Strength, Yield	7.60 MPa	1100 psi	ASTM D638-61T
Elongation at Break	650 %	650 %	ASTM D638-61T

Thermal Properties	Metric	English	Comments
Vicat Softening Point	128 °C	262 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China