

Chevron Phillips 1025 Extrusion Coating Resin (discontinued **)

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

Resin Type: Speed Resin, Base Resin Type - Chevron PE1017
Characteristics: Excellent Processability at 570-620°F (300-325°C) Melt, Good Adhesion at Low Coating Weights and High Speed Lines, Low COF uses, FDA Approved for Food Contact
Applications: Can be used in the outer coextrusion layer or monolayer coating for high slip applications
Data provided by Chevron Chemical.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chevron-Phillips-1025-Extrusion-Coating-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.917 g/cc	0.0331 lb/in ³	ASTM D1505-60T
Melt Flow	7.0 g/10 min	7.0 g/10 min	ASTM D1238-57T

Processing Properties	Metric	English	Comments
Melt Temperature	299 - 327 °C	570 - 621 °F	Excellent Processability

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China