

## ChevronTexaco 60-T White Oil

Category : Fluid , Lubricant , White Mineral Oil (WMO)

### Material Notes:

**Features**Chevron White Oils are technical grade oils processed from paraffinic oil. Mixtures of paraffinic and naphthenic hydrocarbons, they are virtually free of nitrogen, sulfur, oxygen, and aromatic compounds. They approach the quality requirements of food grade white oils.  
**Applications**Chevron White Oils are used in food packaging or handling applications such as:process oilsplasticizersdust control oils or moisture barriers in animal feed manufacturelubricants on machinery of in food packaging such as foilrust preventative formulations for food handlingdefoamersChevron White Oils are recommended for applications where discoloration, staining, or sludging in service must be minimized.In applications where higher temperatures are encountered, such as heating baths or lubricants, greatly extended service life is usually noted when Chevron White Oils, in combination with an antioxidant, are substituted for ordinary mineral oils.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-60-T-White-Oil.php](http://www.lookpolymers.com/polymer_ChevronTexaco-60-T-White-Oil.php)

Physical Properties	Metric	English	Comments
API Gravity	30.8 °	30.8 °	
Saybolt Viscosity at 100°F	606 SUS	606 SUS	
Kinematic Viscosity at 40°C (104°F)	116 cSt	116 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-12.0 °C	10.4 °F	ASTM D97
Flash Point	275 °C	527 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	+25, Saybolt	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China