

ChevronTexaco ATF+3® Automatic Transmission Fluid

Category: Fluid, Lubricant

Material Notes:

General DescriptionDaimlerChrysler has had their own ATF specifications for many years, but as of 1997, Chrysler owners manuals no longer list DEXRON as an acceptable replacement. ATF+3 is a readily available mineral oil-based ATF that is suitable in any application calling for ATF PLUS®, ATF+2®, or a Type 7176® fluid. Vehicles manufactured after 1999 require ATF+4®, a synthetic-based ATF only available through DaimlerChrysler. Chevron ATF+3 is specially formulated to optimize performance of Chrysler transmissions and transaxles. Applications Chevron ATF+3 Automatic Transmission Fluid is designed for use in all Chrysler automatic transmissions and automatic transaxles where a Mopar ATF PLUS, ATF+2 or ATF+3 fluid is specified. It is not recommended for use in transmissions specifying either DEXRON® or MERCON® type fluids Chevron ATF+3 Automatic Transmission Fluid has been registered with the Chrysler Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-ATF3-Automatic-Transmission-Fluid.php

Physical Properties	Metric	English	Comments
API Gravity	31.2°	31.2°	
Brookfield Viscosity	18000 cP	18000 cP	
	@Temperature -40.0 °C	@Temperature -40.0 °F	
Viscosity Measurement	188	188	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	35.9 cSt	35.9 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	7.6 cSt	7.6 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-48.0 °C	-54.4 °F	ASTM D97
Flash Point	194 °C	381 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	Red	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China