ChevronTexaco MERCON® V Automatic Transmission Fluid

Category : Fluid , Lubricant

Material Notes:

Beginning with the 1997 model year, Ford introduced a higher performance level ATF with the MERCON V specification. Many Ford automatic transmissions from 1999 on will require a MERCON V fluid. The most notable exceptions are the E40D, 4R100, and CD4E transmissions, which still specify regular MERCON ATF.Chevron ATF MERCON® is fully approved for MERCON V, as well as DEXRON®-III and MERCON® approved. It provides excellent performance in frigid cold and is formulated to resist viscosity breakdown for long fluid life.ApplicationsChevron Automatic Transmission Fluid MERCON V is designed specifically for use in Ford Motor Compay transmissions that require a MERCON V fluid. The enhanced properties of the MERCON V specification offer premium performance in MERCON or DEXRON-III applications.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-MERCON-V-Automatic-Transmission-Fluid.php

Physical Properties	Metric	English	Comments
API Gravity	30.8 °	30.8 °	
Brookfield Viscosity	11500 сР	11500 cP	
	@Temperature -40.0 °C	@Temperature -40.0 °F	
Viscosity Measurement	194	194	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	202 SUS	202 SUS	
Saybolt Viscosity at 210°F	54 SUS	54 SUS	
Kinematic Viscosity at 40°C (104°F)	40 cSt	40 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	8.4 cSt	8.4 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-45.0 °C	-49.0 °F	ASTM D97
Flash Point	196 °C	385 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	Red	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842



Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China