

ChevronTexaco Marfak® 0

Category : Fluid , Lubricant , Organic Soap Gellant

Material Notes:

Texaco Marfak grease delivers value through: Good film strength Good rust and corrosion protection, even in wet conditions. Texaco Marfak greases are fibrous sodium soap greases. It resists oil separation and protects against dirt and rust. Texaco Marfak grease is formulated to: Protect equipment from dust and dirt by providing a seal Protect equipment against rusting in the presence of small amounts of water. Texaco Marfak greases are recommended for slow speed, plain bearing and general-purpose lubrication of agricultural equipment. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. Notes: Minimum operating temperature is the lowest temperature at which a grease, already in place, could be expected to provide lubrication. Most greases cannot be pumped at these minimum temperatures. Maximum operating temperature is the highest temperature at which the grease could be used with frequent (daily) relubrication. Determined on mineral oil extracted by vacuum filtration. CPS Number: 220927; MSDS Number: 9003

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Marfak-0.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	4853 SUS	4853 SUS	See Note 3.
Saybolt Viscosity at 210°F	181 SUS	181 SUS	See Note 3.
Kinematic Viscosity at 40°C (104°F)	880 cSt	880 cSt	See Note 3.
Kinematic Viscosity at 100°C (212°F)	37 cSt	37 cSt	See Note 3.

Mechanical Properties	Metric	English	Comments
Penetration P(60), 1/10 mm	370	370	Unknown Amount of Work, 25°C (77°F)
Oil Separation	1.7 %	1.7 %	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	93.0 °C	199 °F	See Note 2.
Minimum Service Temperature, Air	-12.0 °C	10.4 °F	See Note 1.
Flash Point	220 °C	428 °F	See Note 3.
Dropping Point	166 °C	331 °F	

Descriptive Properties	Value	Comments
Color	Dark Brown	
Rust Prevention	Pass	

Descriptive Properties Texture	Value stringy	Comments
Thickener, %	7	Sodium

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China