

Chosun Refractories BATN-D2, Lower Gas Purging Refractory

Category : Ceramic , Oxide , Aluminum Oxide

Material Notes:

Information provided by Chosun Refractories via Korea Institute of Ceramic Engineering and Technology (KICET).

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chosun-Refractories-BATN-D2-Lower-Gas-Purging-Refractory.php

Physical Properties	Metric	English	Comments
Bulk Density	2.70 - 2.80 g/cc	0.0975 - 0.101 lb/in³	
Porosity	21 - 24 %	21 - 24 %	

Mechanical Properties	Metric	English	Comments
Compressive Strength	<= 19.6 MPa	<= 2840 psi	Cold Crushing Strength

Thermal Properties	Metric	English	Comments
CTE, linear	5.00 µm/m-°C	2.78 µin/in-°F	
	@Temperature 1000 °C	@Temperature 1830 °F	

Component Elements Properties	Metric	English	Comments
Al2O3	87 - 93 %	87 - 93 %	

Descriptive Properties	Value	Comments
Main Application	Porous nozzle, Sharp and homogeneous pore size distribution, Double structure for anticlogging	
Permeability(?,cm/?,sec,h2o,cm)	1.3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China