

Colorite Polymers Weatherflex™ CS1534WX (NTL01P) Wire and Cable Vinyl Compound

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Wire and Cable Grade

Material Notes:

Description: Colorite specialty wire and cable compounds feature low smoke properties, excellent flame retardance, low temperature flexibility, and resistance to abrasion and chemicals. All are available in UL and non-UL grades. In addition, the engineering-grade thermoplastic elastomers we offer can stand up to the most demanding applications . . . while providing the most desirable performance characteristics at a cost that's more affordable than "ordinary" elastomers. Typical Applications: Leaded audio cable jacketInformation provided by Colorite Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Colorite-Polymers-Weatherflex-CS1534WX-NTL01P-Wire-and-Cable-Vinyl-Compound.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.31 g/cc	1.31 g/cc	ASTM D792
Loss On Ignition	28 %	28 %	ASTM 2863

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	74	74	10 sec; ASTM D2240
Tensile Strength, Ultimate	11.0 MPa	1600 psi	ASTM D412
Elongation at Break	300 %	300 %	ASTM D412

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	90.0 °C	194 °F	
Brittleness Temperature	-45.0 °C	-49.0 °F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China