

ConocoPhillips 85W-140 Universal Gear Lubricant

Category : Fluid , Lubricant

Material Notes:

Description: Conoco Universal Gear Lubricant is an excellent multipurpose, extreme pressure lubricant for differentials and manual transmissions of passenger cars, trucks, vans, buses and off-road equipment that operates under mild to severe service conditions. It is available in two viscosity grades: SAE 80W-90 and SAE 85W-140. Both grades are qualified for API Service GL-5 and MT-1. They meet U.S. Military Specification Mil PRF- 2105E and Mack GO-J. Universal Gear Lubricant can be used in limited-slip differentials for top-off applications. For the complete drain and refill of automotive limited-slip differentials, a special additive is available through local automobile dealerships. Universal Gear Lubricant offers thermal and oxidative stability, as well as maximum protection against gear wear, rust and corrosion. It is also suited for industrial gear drives that call for a AGMA No. 4 or 7 lubricant. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-85W-140-Universal-Gear-Lubricant.php

Physical Properties	Metric	English	Comments
API Gravity	25.6 °	25.6 °	
Viscosity Measurement	95	95	Viscosity Index
Saybolt Viscosity at 100°F	1800 SUS	1800 SUS	
Saybolt Viscosity at 210°F	135 SUS	135 SUS	
Kinematic Viscosity at 40°C (104°F)	360 cSt	360 cSt	
Kinematic Viscosity at 100°C (212°F)	26.5 cSt	26.5 cSt	
ASTM Color	8.0	8.0	

Thermal Properties	Metric	English	Comments
Pour Point	-12.2 °C	10.0 °F	
Flash Point	204 °C	400 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China