

ConocoPhillips Hydroclear® 10W-30 Power-D E.O. 10W-30

Category: Fluid, Lubricant

Material Notes:

Description: Conoco Hydroclear Power-D Engine Oil, formulated from Conoco's premium hydrocracked base stock, protects diesel and gasoline engines against wear, deposits, varnish, rust and corrosion. These performance- proven, heavy-duty engine oils are recommended for both on- and off-road service, including construction, forestry, mining, marine and stationary power generation. They are also recommended for propane and compressed natural gas engines. In Power-D Engine Oil, the exclusive combination of hydrocracked base oils and unique high-performance additives offer excellent soot control, which results in cleaner engines, longer engine life and fewer drain intervals. Hydroclear Power-D Engine Oil SAE 15W40 exceeds the performance requirements of API CH-4; Mack EO-M; EO-M Plus; Cummins CES 20071, 20072, 20076, and 20077; and Volvo VDS and VDS-2, as well as the top EUROPEAN specifications. Hydroclear Power-D Engine Oil, in the appropriate viscosity grades, is recommended for use in most domestic and imported heavy-duty engines. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-10W-30-Power-D-EO-10W-30.php

Physical Properties	Metric	English	Comments
API Gravity	30.7°	30.7°	
Viscosity Measurement	145	145	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	71 cSt	71 cSt	
Kinematic Viscosity at 100°C (212°F)	11 cSt	11 cSt	
Ash	1.35 %	1.35 %	Sulfur
ASTM Color	3.5	3.5	

Thermal Properties	Metric	English	Comments
Pour Point	-45.0 °C	-49.0 °F	
Flash Point	213 °C	415 °F	

Chemical Properties	Metric	English	Comments	
Total Base Number	10.2	10.2		

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China