

ConocoPhillips Syncon® 68 Synthetic AW Hydraulic Fluid 68

Category : Fluid , Lubricant , Polyalphaolefin (PAO)

Material Notes:

Description: Conoco Syncon Synthetic AW Hydraulic Fluid is a synthetic polyalphaolefin (PAO) antiwear fluid for hydraulic systems that operate at extreme temperatures. It is available in four ISO viscosity grades: 22, 32, 46 and 68. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Syncon-68-Synthetic-AW-Hydraulic-Fluid-68.php

Physical Properties	Metric	English	Comments
Density	0.848 g/cc	0.0306 lb/in ³	
Viscosity Measurement	145	145	Viscosity Index
Saybolt Viscosity at 100°F	315 SUS	315 SUS	
Saybolt Viscosity at 210°F	60 SUS	60 SUS	
Kinematic Viscosity at 40°C (104°F)	68 cSt	68 cSt	
Kinematic Viscosity at 100°C (212°F)	10.3 cSt	10.3 cSt	
ASTM Color	1.5	1.5	

Thermal Properties	Metric	English	Comments
Pour Point	-53.9 °C	-65.0 °F	
Flash Point	266 °C	510 °F	

Electrical Properties	Metric	English	Comments
Dielectric Strength	40.0 kV/mm	1020 kV/in	No thickness given

Chemical Properties	Metric	English	Comments
Total Acid Number	0.70	0.70	

Descriptive Properties	Value	Comments
ASTM Rust A&B	Pass	
Copper Corrosion	1A	
Emulsion Characteristics (40-37-3)	Max 10 minutes	
Vickers 35VQ-25 Pump Test	Pass	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China