

## Covestro Bayfill® EA 2001 Polyurethane Energy-Absorbing Semi-Rigid Foam, Friable Grade, MDI-based 2-Component Liquid System

Category: Polymer, Thermoset, Polyurethane, TS, Thermoset Polyurethane Foam, Unreinforced

## **Material Notes:**

Information provided by Bayer Corporation, Polyurethanes DivisionAs of 1 September 2015, Bayer Material Science was separated from

Order this product through the following link:

Bayer AG and officially adopted its new name - Covestro.

http://www.lookpolymers.com/polymer\_Covestro-Bayfill-EA-2001-Polyurethane-Energy-Absorbing-Semi-Rigid-Foam-Friable-Grade-MDI-based-2-Component-Liquid-System.php

Physical Properties	Metric	English	Comments
Density	0.0370 g/cc	0.00134 lb/in³	Molded density, ASTM D1622
Apparent Bulk Density	0.0220 g/cc	0.000795 lb/in³	Free-rise Density, Bayer test
Water Absorption	4.3 %	4.3 %	2.5 hours. Bayer Test
	9.4 %	9.4 %	24 hours. Bayer Test
Linear Mold Shrinkage	0.010 cm/cm	0.010 in/in	Bayer Test

Mechanical Properties	Metric	English	Comments
Compressive Yield Strength	0.180 MPa	26.1 psi	Static, 70% Compression, ASTM D1621

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China