

Covestro Desmopan® DP 3059D Polyurethane

Category : Polymer , Thermoplastic , Polyurethane, TP

Material Notes:

injection molding gradewith release agentexcellent abrasion resistancegood wear resistancevery short cycle timesApplicationHeel patchesRollersBoot shellsInjection molded engineering partsPreprocessingMax. Water content

Order this product through the following link:

http://www.lookpolymers.com/polymer_Covestro-Desmopan-DP-3059D-Polyurethane.php

Physical Properties	Metric	English	Comments
Density	1.23 g/cc	0.0444 lb/in³	ISO 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	97	97	3s; ISO 868
Hardness, Shore D	59	59	15s; ISO 868
Abrasion	18	18	mm³; ISO 4649
Compression Set	24 %	24 %	ISO 815
	@Temperature 23.0 °C	@Temperature 73.4 °F	
	46 %	46 %	ISO 815
	@Temperature 70.0 °C	@Temperature 158 °F	

Descriptive Properties	Value	Comments
Availability	Europe	
	Near East/Africa	
	South and Central America	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China