

DSM Fibre Intermediates Nyrin® 2025 (Wollastocoat®), Conditioned

Category : Polymer , Thermoplastic , Nylon , Nylon 6

Material Notes:

Conditioned at 23°C and 50% Relative Humidity. Nyrin is a Block Copolymer of Nylon 6 and an elastomer with exceptional properties in impact resistance, fatigue and abrasion resistance. Nyrin is processed via Reaction Injection Moulding (RIM) technology. Nyrin® is a registered trademark. Information provided by the manufacturer, Brueggemann Chemical.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DSM-Fibre-Intermediates-Nyrin-2025-Wollastocoat-Conditioned.php

Physical Properties	Metric	English	Comments
Density	1.321 g/cc	0.04772 lb/in ³	ISO 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	70	70	ISO 868
Tensile Strength, Ultimate	22.0 MPa	3190 psi	ISO 527
Elongation at Break	50 %	50 %	ISO 527
Modulus of Elasticity	1.75 GPa	254 ksi	ISO 527
Flexural Modulus	1.70 GPa	247 ksi	ISO 178
Izod Impact, Notched (ISO)	10.0 kJ/m ²	4.76 ft-lb/in ²	ISO 180
Charpy Impact, Notched	1.00 J/cm ²	4.76 ft-lb/in ²	DIN 53453
	0.500 J/cm ²	2.38 ft-lb/in ²	DIN 53453
	@Temperature -40.0 °C	@Temperature -40.0 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China