

Denka VINYKON G5369 PVC, W grade for non-migratory sheath and special items

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

A PVC resin compound offering excellent physical properties and workability. A broad product lineup is available, including hard and soft grades, as well as those for extrusion and injection molding, etc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Denka-VINYKON-G5369-PVC-W-grade-for-non-migratory-sheath-and-special-items.php

Physical Properties	Metric	English	Comments
Density	1.267 g/cc	0.04577 lb/in ³	JIS-Z-8807
Deformation	15 %	15 %	JIS-K-6723

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	69	69	JIS-K-6301
Tensile Strength at Break	17.658 MPa	2561.1 psi	JIS-K-6723
Elongation at Break	380 %	380 %	JIS-K-6723
100% Modulus	0.005886 GPa	0.8537 ksi	JIS-K-6723

Thermal Properties	Metric	English	Comments
Minimum Service Temperature, Air	-47.0 °C	-52.6 °F	JIS-K-6723

Electrical Properties	Metric	English	Comments
Volume Resistivity	1.00e+11 ohm-cm @Temperature 30.0 °C	1.00e+11 ohm-cm @Temperature 86.0 °F	JIS-K-6723

Descriptive Properties	Value	Comments
Heating: Retention Rate of Elongation, %	94	JIS-A-5756
Heating: Retention Rate of Tensile Strength, %	94	JIS-A-5756
Oil Resistance: Retention of Tensile Strength, %	95	JIS-K-6723
Oil Resistance: Retention Rate of Elongation, %	80	JIS-K-6723
Thermostability, min, JIS-K-6723	>240	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China