

Dielectric Polymers NT-101PLT Double Liner Tape (discontinued **)

Category : Polymer , Adhesive , Tape , Thermoset , Acrylic/Cyanoacrylate Adhesive

Material Notes:

Acrylic adhesive with moisture stable PE coated kraft base release and high density PE interliner. Features: Clear releases liner allows easy inspection of back lighted panels. Plasticizer migration resistant. Chemical resistant. Applications: Mounting nameplates, graphic panels and decorative trim. Bonding a wide variety of substrates. Information provided by Dielectric Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dielectric-Polymers-NT-101PLT-Double-Liner-Tape-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Adhesive
	76.2 microns	3.00 mil	Interliner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.614 kN/m	3.50 pli	180° peel, PET/s.s.

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	116 °C	240 °F	Shear Adhesive Failure (cohesive failure)
	121 °C	250 °F	Continuous
	204 °C	400 °F	Intermittent
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	Continuous

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China