

Dielectric Polymers NT-2822 Ultra Tack Tape (discontinued **)

Category : Polymer , Adhesive , Tape , Thermoset , Polyester , TS , Silicone

Material Notes:

Crosslinked silicone adhesive with polyester film backing. Features: Chemical resistant Temperature resistant Good conformability Applications: Splicing of silicone coated paper and film at zero wet out time. For applications where instant adhesion is critical. Information provided by Dielectric Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dielectric-Polymers-NT-2822-Ultra-Tack-Tape-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Adhesive
	50.8 microns	2.00 mil	Backing

Mechanical Properties	Metric	English	Comments
Elongation at Break	90 %	90 %	
Peel Strength	0.5478 kN/m	3.125 pli	Adhesion
	8.77 kN/m	50.0 pli	Tensile

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	177 °C	350 °F	
	>= 260 °C	>= 500 °F	Shear Adhesive Failure (polyester failure)
Minimum Service Temperature, Air	-51.1 °C	-60.0 °F	

Descriptive Properties	Value	Comments
Color	Burgundy	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China