

Dielectric Polymers NT-702 Acrylic Tape (discontinued **)

Category : Polymer , Adhesive , Tape , Thermoset , Acrylic/Cyanoacrylate Adhesive

Material Notes:

Acrylic adhesive with polyester film backing. Features: Chemical resistant Temperature resistant Good conformability Applications: Splicing of non-silicone coated substrates. Provides high temperature shear properties, excellent adhesion and solvent resistance. Information provided by Dielectric Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dielectric-Polymers-NT-702-Acrylic-Tape-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Thickness	38.1 microns	1.50 mil	Adhesive
	50.8 microns	2.00 mil	Backing

Mechanical Properties	Metric	English	Comments
Elongation at Break	90 %	90 %	
Peel Strength	0.6793 kN/m	3.875 pli	Adhesion
	8.77 kN/m	50.0 pli	Tensile

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	177 °C	350 °F	
	232 °C	450 °F	Intermittent
	232 °C	450 °F	Shear Adhesive Failure (cohesive failure)
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	

Descriptive Properties	Value	Comments
Color	Various	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China