

Dow Corning 1503 Fluid

Category : Fluid

Material Notes:

A blend of an ultra high viscosity dimethiconol in a low viscosity dimethicone fluid for use in skincare, woundcare, scar therapy, suncare, and color cosmetic applications. Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Corning-1503-Fluid.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.920 g/cc	0.920 g/cc	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity Measure	1500 cSt	1500 cSt	kinetic/kinematic

Thermal Properties	Metric	English	Comments
Flash Point	>= 105 °C	>= 221 °F	closed cup

Optical Properties	Metric	English	Comments
Refractive Index	1.397	1.397	

Processing Properties	Metric	English	Comments
Shelf Life	30.0 Month	30.0 Month	

Descriptive Properties	Value	Comments
Active Content (%)	100	
Cyclotetrasiloxane Content (max %)	0.94	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China