

Dow Corning 2-2617 Diesel Antifoam

Category : Fluid

Material Notes:

100% active polysilicone polyether copolymer, used to control foam in diesel fuel. Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Corning-2-2617-Diesel-Antifoam.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.05 g/cc	1.05 g/cc	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity Measure	200 cSt	200 cSt	Kinetic/Kinematic

Thermal Properties	Metric	English	Comments
Melting Point	<= -7.00 °C	<= 19.4 °F	
Flash Point	80.0 °C	176 °F	Closed cup

Processing Properties	Metric	English	Comments
Shelf Life	30.0 Month	30.0 Month	

Descriptive Properties	Value	Comments
Color	Clear, Light Straw	
Silicone HLB Content (%)	17	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China