

Dow Corning 3225C Formulation Aid

Category: Fluid, Other Engineering Material, Additive/Filler for Polymer

Material Notes:

Dispersion of high molecular weight silicone surfactant in volatile dimethylsiloxane, designed to prepare water-in-silicone emulsions. Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Corning-3225C-Formulation-Aid.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.956 g/cc	0.956 g/cc	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Thermal Properties	Metric	English	Comments
Melting Point	<= 7.00 °C	<= 44.6 °F	
Flash Point	60.0 °C	140 °F	Closed cup

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Color	Translucent White	
Cyclotetrasiloxane Content (%)	<67.5	
Nonvolatile Content (%)	10.5	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China