

Dow Corning MOLYKOTE® PG-21 PLASTISLIP GREASE

Category : Fluid , Lubricant , Silicone Base

Material Notes:

Silicone grease especially for plastic/plastic and plastic/metal combinations like control cables and circuit lever system
Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Corning-MOLYKOTE-PG-21-PLASTISLIP-GREASE.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.960 g/cc	0.960 g/cc	
	@ Temperature 25.0 °C	@ Temperature 77.0 °F	
Kinematic Viscosity	200 cSt	200 cSt	

Mechanical Properties	Metric	English	Comments
Four Ball Extreme Pressure, Weld Load	163.1 kg	359.6 lb (mass)	
Penetration P(60), 1/10 mm	265 - 295	265 - 295	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	190 °C	374 °F	
Minimum Service Temperature, Air	-50.0 °C	-58.0 °F	
Dropping Point	250 °C	482 °F	

Processing Properties	Metric	English	Comments
Shelf Life	60.0 Month	60.0 Month	

Descriptive Properties	Value	Comments
Color	white	
NLGI Number	2	
Water Resistant	yes	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China