

Dow Corning SILASTIC® T-2 RTV SILICONE TRANSLUCENT BASE & CURING AGENT

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Silicone , Silicone Rubber

Material Notes:

Translucent, high strength silicone mold making rubber suited for prototype design and production tooling. Silastic T-2 is recommended for use with rigid polyurethane and can be used with polyesters, foam polyurethane, cement and plaster. Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Corning-SILASTIC-T-2-RTV-SILICONE-TRANSLUCENT-BASE-CURING-AGENT.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.12 g/cc	1.12 g/cc	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity	55000 cP	55000 cP	mixing, dynamic

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	42	42	
Tensile Strength, Ultimate	5.52 MPa	800 psi	
Elongation at Break	300 %	300 %	
Tear Strength	21.0 kN/m	120 pli	

Descriptive Properties	Value	Comments
Appearance	translucent	
Approximate De-mold Time (hours)	10	
Mix Ratio (X:1)	10	Base to Catalyst
Working Time (min)	60	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China