

## **Dow Latex LXC 8429NA Carboxylated Styrene-Butadiene Latex**

Category: Polymer, Thermoplastic, Styrene-Butadiene

## **Material Notes:**

Applications: Latex LXC 8429NA for carpet is a soft hand latex and is used in applications where a soft carpet hand is desired. These applications include some commercial and residential carpets, rugs and woven carpets. Benefits: Soft hand Excellent adhesion Low tack Self curing Low odor Excellent mechanical stability Excellent filler acceptance Information provided by Styron

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Dow-Latex-LXC-8429NA-Carboxylated-Styrene-Butadiene-Latex.php

Physical Properties	Metric	English	Comments
Solids Content	52 %	52 %	
Particle Size	1.4 µm	1.4 µm	
рН	7.85	7.85	
Brookfield Viscosity	180 cP	180 cP	#2 @ 50 rpm

Thermal Properties	Metric	English	Comments	
Glass Transition Temp, Tg	-20.0 °C	-4.00 °F		

Descriptive Properties	Value	Comments
Minimum film formation temperature	<34°F	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China