

DuPont Elvax® 880 Ethylene Vinyl Acetate (discontinued **)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

DuPont™ Elvax® 880 is an ethylene-vinyl acetate copolymer resin containing slip and anti-block additives for use in industrial applications. Applications: Elvax® 880 resins can be used for the following applications: molding, compounding and extrusion. Information provided by DuPont™

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Elvax-880-Ethylene-Vinyl-Acetate-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.930 g/cc	0.0336 lb/in³	ASTM D792-ISO 1183
Vinyl Acetate Content	7.5 %	7.5 %	
Melt Flow	1.2 g/10 min @Load 2.16 kg, Temperature 190 °C	1.2 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238, ISO 1133

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	96	96	ASTM D2240-ISO 868
Hardness, Shore D	44	44	ASTM D2240-ISO 868

Thermal Properties	Metric	English	Comments
Melting Point	99.0 °C	210 °F	ASTM D3417- ISO 3146
Vicat Softening Point	82.0 °C	180 °F	ASTM D1525, ISO 306
Brittleness Temperature	-100 °C	-148 °F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China