

DuPont™ Fusabond® M603 Polymer Modifier

Category : Polymer , Thermoplastic , Adhesives, Sealants, and Coatings

Material Notes:

Fusabond® M603 Resin is a random ethylene copolymer, incorporating a monomer which is classified as being a maleic anhydride equivalent for application uses. Fusabond® M603 is used in a variety of applications where adhesion improvements are needed for coatings, or compatibilization is need for compounds. In these applications, the Fusabond® resin is typically dry blended with a polyolefin matrix polymer for further processing. Examples include: Adhesives, Polymer Modification, Wood-Plastic Composites.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Fusabond-M603-Polymer-Modifier.php

Physical Properties	Metric	English	Comments
Density	0.940 g/cc	0.0340 lb/in ³	ASTM D792, ISO 1183
Melt Flow	25 g/10 min @Load 2.16 kg, Temperature 190 °C	25 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238, ISO 1133

Thermal Properties	Metric	English	Comments
Melting Point	108 °C	226 °F	ASTM D3418, ISO 3146

Processing Properties	Metric	English	Comments
Processing Temperature	<= 260 °C	<= 500 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China