

DuPont Performance Polymers AquaStik® AQS-2540 Polychloroprene Latex (discontinued **)

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE)

Material Notes:

Aquastik™ polychloroprene latexes have been designed for the adhesives industry. They provide an environmentally friendly alternative to solvent-borne systems. This grade features post-forming. 59% Solids. Main uses are in adhesives. Initial pH is 12.5. Medium gel polymer type. Potassium salt of disproportionated rosin acids used as emulsifying agent. Medium crystallization rate. Information provided by DuPont Dow Elastomers. This former DuPont Dow Elastomers product line is now produced by DuPont Performance Elastomers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Performance-Polymers-AquaStik-AQS-2540-Polychloroprene-Latex-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	1.12 g/cc	0.0405 lb/in³	Latex
	1.25 g/cc	0.0452 lb/in³	Polymer
Brookfield Viscosity	30 cP	30 cP	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China