

DuPont Performance Polymers Delrin® PC652 NC010 Acetal (POM) (Unverified Data)**

Category : Polymer , Thermoplastic , Acetal (POM) , Acetal Homopolymer, Unreinforced

Material Notes:

Lubricated Medium Viscosity Acetal Homopolymer with Low Wear and Low Friction Developed for the Healthcare Industry Delrin SC652 is a medium viscosity acetal homopolymer with an advanced system of lubricants. It is developed for parts requiring low wearInformation provided by DuPont Performance Polymers

Order this product through the following link:
http://www.lookpolymers.com/polymer_DuPont-Performance-Polymers-Delrin-PC652-NC010-Acetal-POM-nbspUnverified-Data.php

Physical Properties	Metric	English	Comments
Density	1.39 g/cc	0.0502 lb/in³	ISO 1183

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	65.0 MPa	9430 psi	ISO 527-1/-2
Elongation at Break	23 %	23 %	Nominal; ISO 527-1/-2
Elongation at Yield	11 %	11 %	ISO 527-1/-2
Tensile Modulus	3.00 GPa	435 ksi	ISO 527-1/-2
Charpy Impact, Notched	0.700 J/cm²	3.33 ft-lb/in²	ISO 179/1eA

Thermal Properties	Metric	English	Comments
Melting Point	178 °C	352 °F	10°C/min; ISO 11357-1/-3

Descriptive Properties	Value	Comments
Additives	Lubricants	
	Release agent	
Delivery Form	Pellets	
Part Marking Code	>POM-S<	ISO 11469
Processing	Injection Moulding	
Regional Availability	Asia Pacific	
	Europe	
	Global	

Descriptive Properties	Near East/Africa Value	Comments
	North America	
	South and Central America	
Resin Identification	POM-S	ISO 1043

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China