

DuPont Performance Polymers Hytrel® PC988 NC010 Polyester Elastomer TPC-ET (Unverified Data)**

Category : Polymer , Thermoplastic , Polyester, TP , Polyester Thermoplastic Elastomer

Material Notes:

82 Shore D High Performance Polyester Elastomer Developed for the Healthcare IndustryInformation provided by DuPont Performance Polymers

Order this product through the following link:
http://www.lookpolymers.com/polymer_DuPont-Performance-Polymers-Hytrel-PC988-NC010-Polyester-Elastomer-TPC-ET-nbspUnverified-Data.php

Physical Properties	Metric	English	Comments
Density	1.28 g/cc	0.0462 lb/in³	ISO 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	<= 82	<= 82	ISO 868
Tensile Strength at Break	50.0 MPa	7250 psi	ISO 527-1/-2
Elongation at Break	>= 300 %	>= 300 %	ISO 527-1/-2
Charpy Impact, Notched	1.50 J/cm²	7.14 ft-lb/in²	ISO 179/1eA

Thermal Properties	Metric	English	Comments
Melting Point	221 °C	430 °F	10°C/min; ISO 11357-1/-3

Descriptive Properties	Value	Comments
Delivery Form	Pellets	
Part Marking Code	>TPC-ET<	ISO 11469
Processing	Calandering	
	Casting	
	Coatable	
	Film Extrusion	
	Injection Moulding	
	Other Extrusion	
	Profile Extrusion	
	Sheet Extrusion	

Descriptive Properties	Value	Comments
Regional Availability	Asia Pacific	
	Europe	
	Global	
	Near East/Africa	
	North America	
	South and Central America	
Resin Identification	TPC-ET	ISO 1043
Special Characteristics	High impact or impact modified	
	Light stabilised or stable to light	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China