

DuPont Performance Polymers Kalrez® 6375UP FFKM Perfluoroelastomer

Category: Polymer, Thermoset, Fluoropolymer, TS, Thermoset Fluoroelastomer, Rubber or Thermoset Elastomer (TSE)

Material Notes:

Resists chemical attack and is formulated and processed to minimize the potential for undesirable contaminants. Kalrez® 6375UP has the best balance of performance characteristics required for semicon wet processing environments. Information provided by manufacturer. This former DuPont Dow Elastomers product line is now produced by DuPont Performance Elastomers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Performance-Polymers-Kalrez-6375UP-FFKM-Perfluoroelastomer.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	75	75	ASTM D2240
100% Modulus	0.00720 GPa	1.04 ksi	ASTM D412
Compression Set	30 %	30 %	70 hr; ASTM D395, pellets
	@Temperature 204 °C	@Temperature 399 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	275 °C	527 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China