

## DuPont Teijin Films Teijin® Tetoron® HB3 Polyester Film, 300 Gauge

Category: Polymer, Film, Thermoplastic, Polyester, TP, Polyester Film

## **Material Notes:**

Teijin® Tetoron® HB3 is a super smooth polyester film with a UV absorbing agent, originally designed for green house applications. It has excellent weather-durability, low color and low haze. It is pretreated on one side for slip and is available plain or knurled. Typical Applications: Greenhouse filmOpen air LabelsSolar Window FilmInformation provided by DuPont.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_DuPont-Teijin-Films-Teijin-Tetoron-HB3-Polyester-Film-300-Gauge.php

Mechanical Properties	Metric	English	Comments
Film Elongation at Break, MD	140 %	140 %	ASTM D882A
Film Elongation at Break, TD	100 %	100 %	ASTM D882A
Coefficient of Friction, Dynamic	0.31	0.31	ASTM D1894
Coefficient of Friction, Static	0.33	0.33	ASTM D1894
Film Tensile Strength at Break, MD	264.93 MPa	38425 psi	ASTM D882A
Film Tensile Strength at Break, TD	283.9 MPa	41180 psi	ASTM D882A

Thermal Properties	Metric	English	Comments
Shrinkage, MD	1.0 %	1.0 %	Unrestrained
	@Temperature 150 °C, Time 1800 sec	@Temperature 302 °F, Time 0.500 hour	
Shrinkage, TD	1.0 %	1.0 %	Unrestrained
	@Temperature 100 °C, Time 1800 sec	@Temperature 212 °F, Time 0.500 hour	

Optical Properties	Metric	English	Comments
Haze	0.50 %	0.50 %	ASTM D1003

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China