

Entec Hypel® PELLD60/.925 LLDPE (discontinued **)

Category : Polymer , Thermoplastic , Polyethylene (PE) , LLDPE , Linear Low Density Polyethylene (LLDPE), Injection Molded

Material Notes:

Entec's proprietary products include a full range of compounds in the Nylon 6/6, Nylon 6, ABS, PBT, Polycarbonate, PC/ABS, PC/ASA, PC/PBT, and PPO/PPE resin families. Information provided by Entec.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Entec-Hypel-PELLD60925-LLDPE-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.925 g/cc	0.0334 lb/in ³	ASTM D792
Melt Flow	60 g/10 min @Load 2.16 kg, Temperature 190 °C	60 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	12.8 MPa	1850 psi	ASTM D638
Elongation at Break	90 %	90 %	ASTM D638
Tensile Modulus	0.352 GPa	51.0 ksi	ASTM D638

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China